

CE-B2313AHDS CE-B2320AHDS



FEATURES

- 1/3" HD Sensor
- 1.3 Megapixel, 960p/1.3Mp@25/30fps
- 2.0 Megapixel, 1080p/2.0Mp@25/30fps
- Mini. Illumination: 0.01LUX
- Lens: 3.6/6mm Megapixel Lense
- LED: 36pcs Korea Black LED, 30m IR Distance
- Waterproof: IP67
- Power: DC 12V, 370mA



AHD 2.0Mp outdoor in daytime



AHD 1.3Mp indoor at night



TECHNICAL SPECIFICATION



| Model No. | CE-B2313AHDS | CE-B2320AHDS |
|---------------------|---|---|
| Model | IP67 Waterproof Bullet Camera | |
| Sensor | SONY 1/3" Exmor CMOS IMX238 | SONY 1/3" Exmor CMOS IMX222 |
| Chipset | NVP2430H+238 | AHD2431 |
| Output Resolution | AHD 960P /CVBS 1300 TVL | AHD 1080P /CVBS 1300 TVL |
| Signal Sys. | PAL/NTSC | |
| Total Pixel | 1312(H)×1069(V) 1.4M Pixels | 1920(H)×1080(V) 2.0M Pixels |
| Valid Pixel | 1280(H)×1024(V) 1.31M Pixels | |
| Min Illumination | Color 0.02Lux(F1.2,50IRE,AGC ON); | Color:0.01Lux @(F1.2,AGC ON),0 LUX with IR |
| | BW: 0.0008Lux(F1.2,50IRE,AGC ON) | BW: 0.001 Lux @ (F1.2,AGC ON),0 LUX with IR |
| Electric Shutter | PAL 1/50 ~ 1/100,000s NTSC: 1/60 ~ 1/100,000s | |
| WDR | D-WDR | |
| Sens-up | 0-30X | |
| 2D-DNR | off/ low/ medium/ high | |
| 3D-DNR | | |
| Image-frozen | Support | |
| BLC/HLC | | |
| Defogger | 0-2 Level | |
| S/N | > 60dB | |
| White Balance | Auto White balance | |
| Day/Night | Auto/ manual / Color/ BW | |
| Mirror | Horizontal/ Vertical | |
| Privacy Mask | Support | |
| Video Output | 1.0Vp-p compound output, 75Ω | |
| Lens | 3.6/6mm Megapixel Lens | |
| Infrared LED | 36pcs Korea Black LED | |
| IR Distance | 30Meters | |
| Power | DC 12V±50% | |
| Waterproof | IP67 | |
| Working Temperature | -20°C~60°C | |
| Relative Humidity | 10%-90% Non-condensing | |
| Color | White or Korea Grey | |
| Dimensions | Appr. 191.5mm(L)x64.5mm(W)x72mm(H). Ø 60.5(including Bracket) | |
| Net Weight | 800g/pcs | |