

# CE-B1813IPHi



## FEATURES

- 180ms High Speed Transfer
- Multi-Protocol For Smooth Surveillance
- Black IR Led With Elegance
- 3-Axis bracket, IP67 Waterproof

## KEY FEATURES

- Embedded RTOS system, dicaryon 32bits DSP, real hard compression, watchdog timer design, double lightning protection with cable power supply.
- Standard 2.8-12mm megapixel HD focal variation manual lens, 42pcs black LED lights, constant current and voltage IR board design, infrared distance up to 40 meters.
- Waterproof IR Camera, hidden 3Axis bracket, perfect meet IP67 waterproof Level. IR LED lighting, 24 hours monitor, IR-CUT swift, true day color, best night image
- Standard H.264 video compression, high compression ratio, good view quality.
- Adopt intelligent transmission technology (adaptive bandwidth, rate of dynamic adjustment, voice priority, and jitter buffer).
- 1.3 MP, 1.3 MP and 2.0 MP clear images, support double stream output.
- 1.3MP, Color 0.01 Lux@F1.2, B/W 0.001 Lux@F1.2, 0 Lux@F1.2 with IR
- Support standard Onvif, support multi-platform, terminal, and network.
- Support cloud service
- Support IE, Chrome, Firefox, Safari, Opera and other general browser.
- Support Android, IPHONE, IPAD remote real-time monitoring, and mobile monitoring.
- Support Bi-directional audio communication, G.711 Audio encoding standard.
- Support TF card storage, can be stored alarm recording, alarm screen snap, timing video, manual recording & screen snap.
- Support motion detect, linkage photo, recording, trigger email alarm, FTP storage inform methods.
- Support IO Alarm, linkage photo, recording, trigger email alarm, FTP storage inform methods.
- Support WIFI transmission, WER, WPA/WPA2. WPA-PSK/WPA2-PSK encryption methods(Optional).
- Support POE. IEEE802.3af / at adaptive(optional)
- Support firmware remote upgrade.
- Support multiple user access and clients software



SUMIKAWA

# TECHNICAL SPECIFICATION



Model	Model No.	<b>CE-B1813IPHi</b>	
<b>General Function</b>	Model	<b>Vari-Focal IP67 Waterproof IR Bullet Camera</b>	
	Feature	Low Lux	
	CMOS Model	1.3Megapixel, 1/3" Progressive CMOS	
	Illumination		Color 0.01Lux@F1.7
			B/W 0Lux@F1.7(AGC ON)
	Shutter Speed	1/25Sec~ 1/100,000Sec,Shutter Speed Adjustable	
	Lens	Standard 2.8-12mm Mega HD Lens	
	Day&Night	ICR Filter	
DNR	3D DNR		
<b>Compression Standard</b>	Compression Standard	H.264	
	Audio Encoding	G.726/G.722/G.711 Standard, 64Kbps Transfer Speed	
	Output	32 Kbps~8Mbps	
<b>Video efficiency</b>	Effective Pixel	1280*960	
	Video Frame Rate	50Hz:25fps (1280*960) 60Hz: 30fps (1280*960)	
	Image Setting	Brightness, Saturation, Luminance, Contrast Ratio Adjustable Through Client or IE.	
	Model	Auto/Indoor/Outdoor optional	
	Exposure mode	1/50~1/10000S	
	Electronic shutter	HIGH/MIDDLE/LOW Optional	
	AGC	ON/OFF Optional	
	BLC	Support, Area Optional	
<b>Network function</b>	Storage	FTP, Network, Local, NVR recording By ONVIF	
	Protocal	ONVIF Protocal	
	Smart alarm	Motion Detection, Video Loss, Alarm input, linked photo, record, trigger mail alarm notification, FTP recording etc.	
	Support Agreement	support DHCP/DDNS/Email/NTP/PPPOE/UPNP/FTP/RTSP/DAS/P2P etc. network protocol	
	General Function	Mirror,rolling-over,daylight lamp anti- twinkle,OSD, privacy mask	
<b>Interface</b>	Communication Interface	1 RJ45 adaptive Ethernet port	
	Power Interface	1pc	
	BNC Output	1CH	
	Audio input	N/A	
	Audio output	N/A	
	Extended Interface	POE(Optional)	
<b>Other standard</b>	Working Environment	Environment Temperature-30°C~+60°C Camera Temperature: 25°C~35°C Humidity: <95%	
	Power	DC12V±10%	
	Power Consumption	6W - MAX 12W (ICR on 10-12W)	
	LED	42pcs Korea Black LED	
	IR Distance	40m IR Distance	
	Waterproof Degree	IP67	
	Size(mm)	275× 97 × 88 mm	
	Weight	1.65 Kg~ 1.75 Kg	

